


CENTROLEN**PP LF**Polypropylene
electrically conductive

Rods

Diameter mm	Tolerance diameter mm	Stock lengths mm	Weight black kg/m
20	+ 0,2	+ 1,2	1000 2000
22	+ 0,2	+ 1,2	1000 2000
25	+ 0,2	+ 1,2	1000 2000
28	+ 0,2	+ 1,2	1000 2000
30	+ 0,2	+ 1,2	1000 2000
32	+ 0,2	+ 1,3	1000 2000
35	+ 0,2	+ 1,3	1000 2000
40	+ 0,2	+ 1,5	1000 2000
45	+ 0,3	+ 2,0	1000 2000
50	+ 0,3	+ 2,0	1000 2000
55	+ 0,3	+ 2,0	1000 2000
60	+ 0,3	+ 2,3	1000 2000
65	+ 0,3	+ 2,5	1000 2000
70	+ 0,3	+ 2,5	1000 2000
75	+ 0,4	+ 3,0	1000 2000
80	+ 0,4	+ 3,0	1000 2000
85	+ 0,5	+ 3,4	1000 2000
90	+ 0,5	+ 3,4	1000 2000
100	+ 0,6	+ 3,8	1000 2000
110	+ 0,7	+ 4,2	1000 2000
120	+ 0,8	+ 4,6	1000 2000
125	+ 0,8	+ 4,6	1000 2000
130	+ 0,9	+ 5,4	1000 2000
135	+ 0,9	+ 5,4	1000 2000
140	+ 0,9	+ 5,4	1000 2000
150	+ 1,0	+ 5,8	1000 2000
160	+ 1,1	+ 6,3	1000 2000
170	+ 1,2	+ 7,4	1000 2000
180	+ 1,2	+ 7,4	1000 2000
200	+ 1,3	+ 8,5	1000 2000
225	+ 1,5	+ 9,5	1000 2000
250	+ 1,5	+ 9,5	1000 2000
280	+ 1,5	+ 10,0	1000 2000
300	+ 1,5	+ 10,5	1000 2000
350	+ 1,5	+ 12,0	1000 2000

Tubes

Diameter mm	Tolerances outer diameter mm	Tolerances inner diameter mm	Stock lengths mm	Weight black kg/m
----------------	------------------------------------	------------------------------------	---------------------	----------------------

Tubes made of Centrolen | PP LF are available on request.

PRODUCT INFORMATION

Trade name:	Centrolen	Shapes:	Rods, Tubes
Abbreviation:	PP LF	Colour:	Black
Designation:	Polypropylene electrically conductive	Density:	1,04 g/cm ³

Additional dimensions are available on request.

Tolerance length: 0% bis + 3%

Tolerance width:

10/2020