



Rods

Diameter mm	Tolerance diameter mm		Stock lengths mm	Weight natural kg/m	Weight black kg/m
10	+ 0,1	+ 0,7	1000 3000	0,153	0,153
12	+ 0,2	+ 0,8	1000 3000	0,222	0,222
15	+ 0,2	+ 0,8	1000 3000	0,341	0,341
16	+ 0,2	+ 0,8	1000 3000	0,386	0,386
18	+ 0,2	+ 0,8	1000 3000	0,486	0,486
20	+ 0,2	+ 0,8	1000 3000	0,596	0,596
22	+ 0,2	+ 1,0	1000 3000	0,725	0,725
25	+ 0,2	+ 1,0	1000 3000	0,930	0,930
28	+ 0,2	+ 1,0	1000 3000	1,161	1,161
30	+ 0,2	+ 1,0	1000 3000	1,329	1,329
32	+ 0,2	+ 1,2	1000 3000	1,517	1,517
36	+ 0,2	+ 1,2	1000 3000	1,911	1,911
40	+ 0,2	+ 1,2	1000 3000	2,351	2,351
45	+ 0,3	+ 1,3	1000 3000	2,977	2,977
50	+ 0,3	+ 1,3	1000 3000	3,662	3,662
56	+ 0,3	+ 1,3	1000 3000	4,578	4,578
60	+ 0,3	+ 1,6	1000 3000	5,271	5,271
65	+ 0,3	+ 1,6	1000 3000	6,172	6,172
70	+ 0,3	+ 1,6	1000 3000	7,143	7,143
75	+ 0,4	+ 2,0	1000 3000	8,239	8,239
80	+ 0,4	+ 2,0	1000 3000	9,356	9,356
85	+ 0,5	+ 2,2	1000 3000	10,580	10,580
90	+ 0,5	+ 2,2	1000 3000	11,841	11,841
95	+ 0,6	+ 2,5	1000 3000	13,228	13,228
100	+ 0,6	+ 2,5	1000 3000	14,633	14,633
110	+ 0,7	+ 3,0	1000 3000	17,752	17,752
115	+ 0,8	+ 3,5	1000 3000	19,474	19,474
120	+ 0,8	+ 3,5	1000 3000	21,172	21,172
125	+ 0,8	+ 3,5	1000 3000	22,941	22,941
130	+ 0,9	+ 3,8	1000 3000	24,856	24,856
140	+ 0,9	+ 3,8	1000 3000	28,754	28,754
150	+ 1,0	+ 4,2	1000 3000	33,043	33,043
160	+ 1,1	+ 4,5	1000 3000	37,608	37,608
165	+ 1,2	+ 5,0	1000 3000	40,097	40,097
180	+ 1,2	+ 5,0	1000 3000	47,572	47,572
200	+ 1,3	+ 5,5	1000 3000	58,705	58,705

Tubes

Diameter mm	Tolerances outer diameter mm	Tolerances inner diameter mm	Stock lengths mm	Weight natural kg/m	Weight black kg/m
Tubes made of Centroflon PVDF are available on request.					

Additional dimensions are available on request.

Tolerance length: 0% bis + 3%

Tolerance width:

■ Standard item (available from stock)

Plates

Thickness mm	Tolerance thickness mm		Width mm	Stock lengths mm	Weight natural kg/m	Weight black kg/m
10	+ 0,2	+ 1,1	500	1000 3000	11,084	11,084
10	+ 0,2	+ 1,1	610	1000 3000	13,523	13,523
12	+ 0,3	+ 1,5	500	1000 3000	12,931	12,931
12	+ 0,3	+ 1,5	610	1000 3000	15,776	15,776
15	+ 0,3	+ 1,5	500	1000 3000	15,702	15,702
15	+ 0,3	+ 1,5	610	1000 3000	19,157	19,157
20	+ 0,3	+ 1,5	500	1000 3000	20,321	20,321
20	+ 0,3	+ 1,5	610	1000 3000	24,791	24,791
25	+ 0,3	+ 1,5	500	1000 3000	24,939	24,939
25	+ 0,3	+ 1,5	610	1000 3000	30,426	30,426
30	+ 0,5	+ 2,5	500	1000 3000	29,558	29,558
30	+ 0,5	+ 2,5	610	1000 3000	36,060	36,060
35	+ 0,5	+ 2,5	500	1000 3000	34,176	34,176
35	+ 0,5	+ 2,5	610	1000 3000	41,695	41,695
40	+ 0,5	+ 2,5	500	1000 3000	38,794	38,794
40	+ 0,5	+ 2,5	610	1000 3000	47,329	47,329
45	+ 0,5	+ 2,5	500	1000 3000	43,413	43,413
45	+ 0,5	+ 2,5	610	1000 3000	52,964	52,964
50	+ 0,5	+ 2,5	500	1000 3000	48,031	48,031
50	+ 0,5	+ 2,5	610	1000 3000	58,598	58,598
60	+ 0,5	+ 3,5	500	1000 3000	57,268	57,268
60	+ 0,5	+ 3,5	610	1000 3000	69,867	69,867
70	+ 0,5	+ 3,5	500	1000 3000	66,505	66,505
70	+ 0,5	+ 3,5	610	1000 3000	81,136	81,136
80	+ 0,5	+ 5,0	610	1000 3000	93,250	93,250
90	+ 0,5	+ 5,0	610	1000 3000	104,518	104,518
100	+ 0,5	+ 5,0	610	1000 3000	115,787	115,787

PRODUCT INFORMATION

Trade name: Centroflon
 Abbreviation: PVDF
 Designation: Polyvinylidene fluoride

Shapes: Rods, Tubes, Plates
 Colour: Natural, Black
 Density: 1,78 g/cm³

Additional dimensions are available on request.

Tolerance length: 0% bis + 3%

Tolerance width: + 0,5% bis + 4%

■ Standard item (available from stock)